

ALS 204 LABELING SOLUTION FOR TOP LABELING

Right Hand Version

DESCRIPTION

With this application, labels between 10 - 106 mm width (material width incl. backing paper max. 110 mm) can be applied on the top of products. The surface of the products needs to be flat to secure the smooth application of labels. Paper and stiff PE label materials can be used. The maximum apply speed is 40 m/min. The support stand with vertical and horizontal lead screws enables flexible integration onto a conveyor. The product start sensor has to be connected to the M12 plug on the ALS.


MAIN SPECIFICATIONS ALS 204				
Dispensing speed:	Up to 40 m/min			
Material width incl. backing paper:	10 - 110 mm			
Label length:	5 - 600 mm			
Label roll diameter:	300 mm			
Data Interfaces:	RS 232C, Ethernet, USB			

IMPORTANT BENEFITS

- Flexible integration in your product line
- Attractive price-performance ratio
- Fast and durable for demanding applications
- High apply speed up to 40 m/min
- Material width up to 110 mm
- Accurate label positioning
- Easy vertical and horizontal adjustment of the ALS by means of the lead screws


FOLLOWING PARTS ARE INCLUDED:

POS-NB.	DESCRIPTION	QT
1	ALS 204 RH	1
2	L-shape dispensing edge fixture RH 110 mm	1
3	L-shape fixed dispensing edge RH 110 mm	1
4	Flange plate assembly	1
5	Single H-Foot	1
6	Horizontal lead screw 390 mm	1
7	Vertical lead screw 1.500 mm	1
8	Cross clamp	1
9	Product start sensor	1
10	Extension cable 1.5 m	1






TYPICAL APPLICATIONS: TOP LABELING



Mainly applicable for labeling of products in the same height. Almost all common types of label shapes are supported.

LABELS PER MINUTE (Q) FOR TOP LABELING ALS

EXAMPLES	PRODUCT LENGTH (P)	APPLY SPEED (V)				
		15 M/MIN	20 M/MIN	30 M/MIN	40 M/MIN	
Products:	1. 60 mm long + product distance 20 mm (P)	188	250	375	500	
	2. 100 mm long + product distance 20 mm (P)	125	167	250	333	



As application-specific circumstances can impact the real volumes and apply-speeds, no rights can be derived from these calculations.

Remote display

Calculation of max. labels per minute: $Q = V \times 1000 / P$ Calculation of max. apply speed: $V = Q \times P / 1000$

OPTIONS* FOR ENHANCEMENT OF THIS SOLUTION

- Capacitive label sensor (including bracketry)
- Cable for tandem application
- Interface cable for tandem
- Remote display
- IP65 Protection Kit IP BASIC
- IP65 Protection Kit IT 1
- IP65 Protection Kit IT 2
- Encoder set APSF: Rotary Encoder (for APSF), incl. cable with M12-plug
- External OD control (RH)
- * not included, have to be ordered separately.

The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. NOVEXX Solutions shall have no liability whatsoever, regardless of any legal theory, arising out of your use or reliance on the information contained herein and in no event shall NOVEXX Solutions be held liable for consequential, indirect or incidental damages. NOVEXX Solutions liability is limited to the replacement value of defective product. Products, information and specifications are subject to change without notice.

© 2015 Novexx Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).

Novexx Solutions GmbH DEUTSCHLAND

Ohmstrasse 3 D-85386 Eching Tel. +49 (0)8165 925 299 info.deutschland@novexx.com

Novexx Solutions S.A.S. FRANCE

Tel. +33 (0)825 82 61 52 info.france@novexx.com

Novexx Solutions B.V. NEDERLAND

Tel. +31 (0)302 63 22 33 info.nederland@novexx.com

Novexx Solutions B.V. BELGIE

Tel. +32 (0)2 377 8002 info.belgie@novexx.com

Novexx Etiketleme Sistemleri Tic. A.Ş. TÜRKIYE

Tel. +90 216 564 81 81 info.turkiye@novexx.com

Novexx Solutions GmbH

Tel. +39 0331 1855511 info.italia@novexx.com

Novexx Solutions GmbH FILIAL SVERIGE

Tel. +46 (0)31 68 30 40 info.sverige@novexx.com

manroland India Pvt. Ltd. INDIA

Tel. +91 (11) 47002900 info.india@novexx.com

Novexx Solutions USA

Tel. +1 610 4730751 info.usa@novexx.com

Novexx Solutions ASIA

Tel. +86 (021) 2215 7665 info.asia@novexx.com

Novexx Solutions GmbH POLSKA

Tel. +48 (0)605957108 info.polska@novexx.com

www.novexx.com